




**HEYsign fabrics**  
**FACING you.** *Setting signs for your success.*










# HEYsign banners - FACE your space. Grasping attention with every format.

Application	Article	Coating	Weight	Tensile strength	Width	2 side	FR	Solvent	UV	Latex	HP-cert	
backlit	<b>backlit light eco B1</b> Ref. H6006-0301	PVC	500 g/m <sup>2</sup> 14.7 oz/yd <sup>2</sup>	2900/2500 N/5 cm 331/286 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓			
	<b>backlit light B1</b> Ref. H6005-0301	PVC	500 g/m <sup>2</sup> 14.7 oz/yd <sup>2</sup>	2900/2400 N/5 cm 331/274 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>backlit matt B1/M2</b> Ref. H5505-0302	PVC	650 g/m <sup>2</sup> 19.2 oz/yd <sup>2</sup>	2900/2700 N/5 cm 331/308 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓		
	<b>heylight B1</b> Ref. H5500-0303	PVC	680 g/m <sup>2</sup> 20.2 oz/yd <sup>2</sup>	3400/3300 N/5 cm 388/377 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓		
frontlit	<b>frontlit light eco</b> Ref. H5022-0295	PVC	500 g/m <sup>2</sup> 14.7 oz/yd <sup>2</sup>	2800/2100 N/5 cm 320/240 lbs/inch	320/500 cm 126/197 inch			✓	✓	✓		
	<b>frontlit light eco B1/M2</b> Ref. H6022-0295	PVC	500 g/m <sup>2</sup> 14.7 oz/yd <sup>2</sup>	2700/2200 N/5 cm 308/251 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>frontlit eco B1/M1</b> Ref. H6025-0295	PVC	500 g/m <sup>2</sup> 14.7 oz/yd <sup>2</sup>	2600/2100 N/5 cm 297/240 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>frontlit light B1/M2</b> Ref. H5469-0295	PVC	500 g/m <sup>2</sup> 14.7 oz/yd <sup>2</sup>	2900/2300 N/5 cm 331/264 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>frontlit light B1/M1</b> Ref. H6471-0295	PVC	475 g/m <sup>2</sup> 14 oz/yd <sup>2</sup>	2900/2400 N/5 cm 331/274 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>soft plus outdoor B1/M2</b> Ref. H6804-0291	PVC	350 g/m <sup>2</sup> 10 oz/yd <sup>2</sup>	1500/1300 N/5 cm 171/ 148 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓		
	<b>soft plus B1</b> Ref. H6803-0292	PVC	350 g/m <sup>2</sup> 10 oz/yd <sup>2</sup>	1670/1220 N/5 cm 191/139 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
mesh	<b>soft blueback B1/M2</b> Ref. H6803-B951	PVC	350 g/m <sup>2</sup> 10 oz/yd <sup>2</sup>	1700/1220 N/5 cm 194/139 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>mesh matt eco</b> Ref. H5024-0297	PVC	340 g/m <sup>2</sup> 10 oz/yd <sup>2</sup>	2600/1600 N/5 cm 297/183 lbs/inch	320/500 cm 126/197 inch			✓	✓	✓		
	<b>mesh matt B1/M1</b> Ref. H5071-0290	PVC	340 g/m <sup>2</sup> 10.3 oz/yd <sup>2</sup>	2600/1600 N/5 cm 297/183 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
	<b>mesh SR B1/M1</b> Ref. H5371-0291	PVC	370 g/m <sup>2</sup> 11 oz/yd <sup>2</sup>	1600/1800 N/5 cm 182/205 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
blockout	<b>blockout B1/M2</b> Ref. H3512-0026	PVC	760 g/m <sup>2</sup> 22.4 oz/yd <sup>2</sup>	2900/2500 N/5 cm 330/285 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	
truck	<b>vectaplan panama print</b> Ref. H5551-0290	PVC	900 g/m <sup>2</sup> 26.5 oz/yd <sup>2</sup>	4400/4200 N/5 cm 502/480 lbs/inch	300/320 cm 118/126 inch			✓	✓	✓	✓	
	<b>vectaplan 9/9 print</b> Ref. H5560-0292	PVC	680 g/m <sup>2</sup> 20 oz/yd <sup>2</sup>	3400/3200 N/5 cm 388/365 lbs/inch	250/300 cm 98.4/118 inch			✓	✓	✓	✓	

## HEYsign textiles - FACE your passion. *Wrap the world in bright colors.*




Application	Article	Coating	Weight	Tensile strength	Width	PVC-free							  
						2 sides	FR	Solvent	UV	Dye-Sub	Latex	HP-cert	
backlit	<b>digitex® luxor B1</b> Ref. H7810-5401	PU-acrylic	150 g/m <sup>2</sup> 4.6 oz/yd <sup>2</sup>	430/820 N/5 cm 49/94 lbs/inch	320/510 cm 126/200 inch	✓	✓	✓	✓	✓	✓	  	
	<b>digitex® heylux B1</b> Ref. H7806-0402	acrylic	210 g/m <sup>2</sup> 6 oz/yd <sup>2</sup>	400/1100 N/5 cm 46/126 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	 	
frontlit	<b>digitex® decoflex light B1/M1</b> Ref. H7300-5501	treatment	170 g/m <sup>2</sup> 5 oz/yd <sup>2</sup>	400/1100 N/5 cm 46/126 lbs/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	  	
	<b>digitex® decoflex B1/M1</b> Ref. H7304-5501	treatment	215 g/m <sup>2</sup> 6.3 oz/yd <sup>2</sup>	350/1500 N/5 cm 40/171 lbs/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	 	
	<b>digitex® decoflex premium B1/M1</b> Ref. H7335-5501	treatment	220 g/m <sup>2</sup> 6.5 oz/yd <sup>2</sup>	400/1750 N/5 cm 46/200 lbs/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	 	
	<b>digitex® decoflex display plus B1/M1</b> Ref. H7313-0295	PUR	235 g/m <sup>2</sup> 7 oz/yd <sup>2</sup>	350/1200 N/5 cm 40/137 lbs/inch	up to 500 cm up to 197 inch	✓	✓	✓	✓	✓	✓	  	
	<b>digitex® superior B1/M1</b> Ref. H7835-5296	PU-acrylic	340 g/m <sup>2</sup> 10 oz/yd <sup>2</sup>	1600/4000 N/5 cm 183/457 lbs/inch	320/500 cm 126/197 inch	✓	✓	✓	✓	✓	✓	 	
	<b>digitex® ecotex B1</b> Ref. H7022-0295	EVA	270 g/m <sup>2</sup> 8 oz/yd <sup>2</sup>	2800/24500 N/5 cm 320/280 lbs/inch	up to 500 cm up to 197 inch	✓	✓	✓	✓	✓	✓	   	
blockout	<b>digitex® decoflex opaque B1/M2</b> Ref. H7380-5975	PUR	315 g/m <sup>2</sup> 9 oz/yd <sup>2</sup>	300/1200 N/5 cm 34/137 lbs/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	   	
	<b>digitex® decoflex nightfever B1</b> Ref. H7385-5975	acrylic	260 g/m <sup>2</sup> 8 oz/yd <sup>2</sup>	300/1000 N/5 cm 34/114 lbs/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	   	
	<b>digitex® decoflex whitenight B1</b> Ref. H7390-5126	PU	365 g/m <sup>2</sup> 11 oz/yd <sup>2</sup>	300/1200 N/5 cm 34/137 lbs/inch	up to 505 cm up to 198.8 inch	✓	✓	✓	✓	✓	✓	  	
	<b>digitex® opaque B1/M1</b> Ref. H7880-0026	acrylic	320 g/m <sup>2</sup> 9 oz/yd <sup>2</sup>	670/430 N/5 cm 76/49 lbs/inch	up to 310 cm up to 122 inch	✓	✓	✓	✓	✓	✓	  	

## HEYsign deco - FACE your mood. *Giving a face to free spaces.*

Application	Article	Coating	Weight	Tensile strength	Width	PVC-free			  	
						FR	UV	Latex		
Wall and ceiling coverings	<b>ceistar® premium B1/M1</b> Ref. H7401-5290	PU	290 g/m <sup>2</sup> 8.5 oz/yd <sup>2</sup>	350/1600 N/5 cm 40/183 lbs/inch	320/420/510 cm 126/165/201 inch	✓	✓	✓	✓	  
	<b>ceistar® light B1</b> Ref. H7431-5290	PU	250 g/m <sup>2</sup> 8 oz/yd <sup>2</sup>	90/195 N/5 cm 20/44 lbs/inch	320/510 cm 126/201 inch	✓	✓	✓	✓	  



# HEYsign laminates - FACE your moment. Brilliant quality for the great moment.

Application	Article	Coating	Structure	Weight	Tensile strength	Thickness	Width	2 sides	FR	Solvent	UV	Latex	HP cert.	
backlit	HB-51-W38	PVC	woven	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	1150/1100 N/5 cm 259/247 lbs/2 inch	0,36 mm 14 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	  
	HB-55-W52	PVC	woven	550 g/m <sup>2</sup> 16 oz/yd <sup>2</sup>	1900/1750 N/5 cm 427/393 lbs/2 inch	0,41 mm 16 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	
	HB-51-W16	PVC	woven	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	2200/1800 N/5 cm 495/405 lbs/2 inch	0,39 mm 15 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	
	HB-44-25	PVC	knitted	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	700/600 N/5 cm 157/135 lbs/2 inch	0,32 mm 12 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	
	HB-61-27	PVC	knitted	610 g/m <sup>2</sup> 18 oz/yd <sup>2</sup>	1000/750 N/5 cm 225/169 lbs/2 inch	0,42 mm 17 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	
	HB-61-66	PVC	knitted	610 g/m <sup>2</sup> 18 oz/yd <sup>2</sup>	1200/900 N/5 cm 270/202 lbs/2 inch	0,43 mm 17 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	✓
	HB-65-69	PVC	knitted	650 g/m <sup>2</sup> 19 oz/yd <sup>2</sup>	1600/1300 N/5 cm 360/292 lbs/2 inch	0,47 mm 19 milli inch	320 cm 126 inch	✓*	✓*	✓	✓	✓	✓	
	HBC-51-25	PVC	knitted	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	550/500 N/5 cm 124/112 lbs/2 inch	0,38 mm 15 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
	frontlit	HF-45-W38	PVC	woven	450 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	1200/1100 N/5 cm 270/247 lbs/2 inch	0,32 mm 13 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓
HP-40-W84		PVC	woven	400 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	2000/1600 N/5 cm 450/360 lbs/2 inch	0,32 mm 13 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-51-W16		PVC	woven	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	2200/1800 N/5 cm 495/405 lbs/2 inch	0,39 mm 15 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-32-25		PVC	knitted	320 g/m <sup>2</sup> 9 oz/yd <sup>2</sup>	700/600 N/5 cm 157/135 lbs/2 inch	0,25 mm 10 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-44-25		PVC	knitted	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	700/600 N/5 cm 157/135 lbs/2 inch	0,30 mm 12 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-44-11		PVC	knitted	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	1350/1100 N/5 cm 303/247 lbs/2 inch	0,36 mm 14 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-44-55		PVC	knitted	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	850/600 N/5 cm 191/135 lbs/2 inch	0,32 mm 12 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-51-11		PVC	knitted	510g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	1482/1186 N/5 cm 333/267 lbs/2 inch	0,40 mm 16 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HF-34-25		PVC	knitted	340 g/m <sup>2</sup> 10 oz/yd <sup>2</sup>	700/600 N/5 cm 157/135 lbs/2 inch	0,25 mm 10 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	
HFC-44-W68		PVC	woven	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	1250/1100 N/5 cm 281/247 lbs/2 inch	0,36 mm 14 milli inch	320 cm 126 inch	✓*	✓	✓	✓	✓	✓	

\* additionally available

# HEYsign laminates - FACE your moment. Brilliant quality for the great moment.

Application	Article	Coating Structure		Weight	Tensile strength	Thickness	Width	2 sides	FR	Solvent	UV	Latex	HP cert.	
blockout	HO-44-W38	PVC	woven	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	1200/1100 N/5 cm 270/247 lbs/2 inch	0,31 mm 12 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓	✓	
	HO-51-W38	PVC	woven	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	1200/1100 N/5 cm 270/247 lbs/2 inch	0,36 mm 14 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓	✓	
	HO-61-W16	PVC	woven	610 g/m <sup>2</sup> 18 oz/yd <sup>2</sup>	2340/1599 N/5 cm 526/359 lbs/2 inch	0,43 mm 17 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓		
	HO-51-25	PVC	knitted	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	700/900 N/5 cm 157/202 lbs/2 inch	0,36 mm 14 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓		
	HO-51-27	PVC	knitted	510 g/m <sup>2</sup> 15 oz/yd <sup>2</sup>	700/900 N/5 cm 157/202 lbs/2 inch	0,35 mm 14 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓		
dual color	HF-44-W52 white-black/grey	PVC	woven	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	1900/1700 N/5 cm 427/382 lbs/2 inch	0,33 mm 13 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓		
	HF-44-25 white-black/grey	PVC	knitted	440 g/m <sup>2</sup> 13 oz/yd <sup>2</sup>	700/600 N/5 cm 157/134 lbs/2 inch	0,30 mm 12 milli inch	320 cm 126 inch	✓	✓*	✓	✓	✓	✓	
mesh	HM-26-W11 without liner	PVC	woven	260 g/m <sup>2</sup> 8 oz/yd <sup>2</sup>	1200/1100 N/5 cm 270/225 lbs/2 inch		320 cm 126 inch	✓	✓*	✓	✓			
	HM-26-W12 without liner	PVC	woven	260 g/m <sup>2</sup> 8 oz/yd <sup>2</sup>	1400/1350 N/5 cm 315/303 lbs/2 inch		320 cm 126 inch	✓	✓*	✓	✓			
	HM-26-W51 without liner	PVC	woven	260 g/m <sup>2</sup> 8 oz/yd <sup>2</sup>	1200/1400 N/5 cm 270/315 lbs/2 inch		320 cm 126 inch	✓	✓*	✓	✓			
	HM-32-L11 with liner	PVC	knitted	320 g/m <sup>2</sup> 9 oz/yd <sup>2</sup>	1200/1000 N/5 cm 270/225 lbs/2 inch		320 cm 126 inch	✓	✓*	✓	✓			
	HM-36-L12 with liner	PVC	knitted	360 g/m <sup>2</sup> 11 oz/yd <sup>2</sup>	1400/1350 N/5 cm 315/303 lbs/2 inch		320 cm 126 inch	✓	✓*	✓	✓			

\* additionally available

## ColorBase-Service - Optimize the output of your printer.

For all common quality printing machines we provide and create the desired ICC profile.

Up-to-date and tested ICC color profiles for nearly all media of the HEYtex® brand will be available to Heytex customers free of charge. Link to the database: [heytex.color-base.com](http://heytex.color-base.com)



HP MediaLocator - Profiles for HP Latex certified signs by HEYtex® can be found at HP MediaLocator.


## More about our pictograms | Mehr zu unseren Piktogrammen



backlit



Suitable for DyeSub printing  
*Geeignet für Sublimation*



Tensile strength  
*Höchstzugkraft*



Sewable  
*Nähbar*



frontlit




Flame retardant  
*Schwer entflammbar*



Tear resistance  
*Weiterreißkraft*




Shrinkage  
*Schrumpf*




mesh



Indoor applications  
*Innenanwendungen*



Adhesion  
*Haftung*



Weldable  
*Schweißbar*



blockout



Outdoor applications  
*Außenanwendungen*



Translucency  
*Transluzenz*




UV stabilized  
*UV-stabil*



Suitable for Latex printing  
*Geeignet für Latex-Druck*



Coating  
*Beschichtung*



Width  
*Breite*




Weather resistant  
*Wetterbeständig*




Suitable for Solvent/  
Ecosolvent printing  
*Geeignet für Lösemittel-  
tinten*



Printable on one side  
*einseitig bedruckbar*



Length  
*Länge*



Suitable for UV printing  
*Geeigt für UV-Druck*



Printable on both sides  
*beidseitig bedruckbar*



Foldable  
*Faltbar*

**Heytex Bramsche GmbH**  
Heywinkelstraße 1  
49565 Bramsche  
Germany

T +49 5468 7774-321  
F +49 5468 7774-4321  
heysign@heytex.com  
[www.heytex.com](http://www.heytex.com)

**Heytex USA Inc.**  
T +1 800 255 9338  
info@heytex-usa.com

**Heytex Zhangjiagang Co. Ltd.**  
T +86 512 5699 1002  
china.office@heytex.com

